

**ACCESSORIES FOR DAMPER ACTUATORS**

**FCF...-FCS ...- PCS ...- AH ..- K.. - ZG..**



Code	Description	Data Sheet
<b>FCF 223</b>	End-of-run auxiliary with 2 SPDT switch 3 (0.5) A, 250 V AC for CFS... actuators	–
<b>FCS 223</b>	End-of-run auxiliary with 2 SPDT switch 3 (0.5) A, 250 V AC for CS... actuators	–
<b>PCS 104</b>	Positioner 0...100% for damper actuators 0...10V DC (max. 10 actuators).	–
<b>KH 8</b>	Universal lever for damper shafts (Circle diameter 10...18 mm; Four-square diameter 10...14 mm)	–
<b>AH-25</b>	Lever for actuators CSN ...	–
<b>AH-20</b>	Lever for actuators CSS ...	–
<b>AH-GMA</b>	Lever for actuators CSG ...	–
<b>KG 10</b>	Ball joint for connection (use rods with max. diameter 10 mm)	–
<b>AH-TF</b>	Lever for actuators CFT ...	–
<b>KH-LF</b>	Lever for actuators CFL ...	–
<b>KH-AFB</b>	Lever for actuators CFS ...	–
<b>ZG-NMA</b>	Kit for mounting actuators on the flat CSN ...	–
<b>ZG-SMA</b>	Kit for mounting actuators on the flat CSS ...	–
<b>ZG-GMA</b>	Kit for mounting actuators on the flat CSG ...	–
<b>ZG-TF1</b>	Kit for mounting actuators on the flat CFT ...	–
<b>ZG-LF1</b>	Kit for mounting actuators on the flat CFL ...	–
<b>ZG-AFB</b>	Kit for mounting actuators on the flat CFS ...	–

**Accessories required for coupling actuators to dampers.**

- 1 actuator for 1 damper:
  - direct installation on damper shaft – no accessories required..
  - remote mounting: n° 1 AH...., No. 1 KH8, No. 2 KG 10 and n° 1 rod (¹).
- 1 actuator for 2 dampers:
  - direct installation on shaft of a damper : n° 1 AH...., n° 1 KH8, n° 2 KG 10 e n° 1 asta (¹).
  - remote installation : n° 1 AH...., No. 2 KH8, No. 3 KG 10 and No. 2 rods (¹).
- 1 actuator for 3 dampers:
  - direct installation on shaft of a damper : No. 1 AH...., n° 2 KH8, No. 3 KG 10 and No. 2 rods (¹).
  - remote installation: No. 1 AH...., No. 3 KH8, No. 4 KG 10 and No. 3 rods (¹).

(¹) Connection rods between universal joints 8 ÷ 10 mm. rod (generally available at ironmongers)